

IN THE UNITED STATES
PATENT AND TRADEMARK OFFICE

PATENT APPLICATION

Applicants: **Simon P. VALENTINE, Christopher R. LINZELL,
Lee A. WALKER, Russell K. BULMER**

Case: **3Com-82 (3074US)**

Serial No.:

Filed:

Group Art Unit:

Examiner:

Title: **DISCOVERY OF PHONES ON A NETWORK, SUCH AS A LAN**

Commissioner for Patents
BOX PATENT APPLICATION
Washington, D. C. 20231

S I R:


SUBMISSION OF PRIORITY DOCUMENT

In connection with the above-captioned application, applicants enclose the following priority document to support their claim to priority:

UNITED KINGDOM - Appl. No. 0008671.0, filed
April 7, 2000.

Respectfully submitted,

September 14, 2000


Peter L. Michaelson, Attorney
Reg. No. 30,090
Customer No. 007265
(732) 530-6671

THIS PAGE BLANK (USPTO)


MICHAELSON & WALLACE
Counselors at Law
Parkway 109 Office Center
328 Newman Springs Road
P.O. Box 8489
Red Bank, New Jersey 07701

EXPRESS MAIL CERTIFICATION

"Express Mail" mailing label number: EL632363714US

Date of deposit: September 15, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Commissioner for Patents, **Box Patent Application**, Washington, D.C. 20231.



Signature of person making certification

Peter L. Michaelson

Name of person making certification

THIS PAGE BLANK (USPTO)



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ



the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in the certificate and any accompanying documents has re-registered under the Companies Act 1985 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in the certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed


Dated 16 May 2000

**CERTIFIED COPY OF
PRIORITY DOCUMENT**

THIS PAGE BLANK (USPTO)

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

Cardiff Road
Newport
South Wales
NP9 1RH

1. Your reference

HRW/sb/3Com3074GB

2. Patent application number

(The Patent Office will fill in this part)

0008671.0

07 APR 2000

3. Full name, address and postcode of the or of each applicant (underline all surnames)

3Com Corporation
5400 Bayfront Plaza M/S 1308
Santa Clara
California CA95052 USA

Patents ADP number (if you know it) 7656978001

If the applicant is a corporate body, give the country/state of its incorporation

Delaware, USA

4. Title of the invention

Discovery of Phones on a Network, such as a LAN

5. Name of your agent (if you have one)

BROOKES & MARTIN

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

HIGH HOLBORN HOUSE
52-54 HIGH HOLBORN
LONDON
WC1V 6SE

Patents ADP number (if you know it)

471001 ✓

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

Yes

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

THIS PAGE BLANK (USPTO)

Patents Form 1/77

Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document

Continuation sheets of this form 0
Description 11
Claim(s) 4
Abstract 0
Drawing(s) 4 + 4


10. If you are also filing any of the following,
state how many against each item.

Priority documents -
Translations of priority documents -
Statement of inventorship and right
to grant of a patent (*Patents Form 7/77*) 1
Request for preliminary examination
and search (*Patents Form 9/77*) 1
Request for substantive examination
(*Patents Form 10/77*) 1
Any other documents -
(*please specify*)

11.

I/We request the grant of a patent on the basis of this application.

Signature



Date

6 April 2000

12. Name and daytime telephone number of
person to contact in the United Kingdom

Hugh R Wright

01892 510600

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.*
- Write your answers in capital letters using black ink or you may type them.*
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.*
- Once you have filled in the form you must remember to sign and date it.*
- For details of the fee and ways to pay please contact the Patent Office.*

THIS PAGE BLANK (USPTO)

**Statement of inventorship and of
right to grant of a patent**

The Patent Office

Cardiff Road
Newport
South Wales
NP9 1RH

1. Your reference

HRW/sb/3Com3074GB

2. Patent application number
(if you know it)

0008671.0

07 APR 2000

3. Full name of the or of each applicant

3Com Corporation

4. Title of the invention

Discovery of Phones on a Network, such as a LAN

5. State how the applicant(s) derived the right
from the inventor(s) to be granted a patent

By virtue of the employment of the inventors and their
employment contract


6. How many, if any, additional Patents Forms
7/77 are attached to this form?
(see note (c))

one

7.

I/We believe that the person(s) named over the page (and on
any extra copies of this form) is/are the inventor(s) of the invention
which the above patent application relates to.

Signature



Date

6 April 2000

8. Name and daytime telephone number of
person to contact in the United Kingdom

Hugh R Wright

01892 510600

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there are more than three inventors, please write the names and addresses of the other inventors on the back of another Patents Form 7/77 and attach it to this form.
- d) When an application does not declare any priority, or declares priority from an earlier UK application, you must provide enough copies of this form so that the Patent Office can send one to each inventor who is not an applicant.
- e) Once you have filled in the form you must remember to sign and date it.

THIS PAGE BLANK (continued)

Enter the full names, addresses and postcodes of the inventors in the boxes and underline the surnames

Simon Peter VALENTINE
55 The Horseshoe
Hemel Hempstead
Hertfordshire
HP3 8QS
United Kingdom

Patents ADP number (if you know it): 78 31241001

Christopher Robert LINZELL
1 Sandfield Road
St Albans
Hertfordshire
AL1 4JZ
United Kingdom

Patents ADP number (if you know it): 78 73383001

Lee Anthony WALKER
126 Estcourt Road
Watford
Hertfordshire
WD1 2PZ
United Kingdom

Patents ADP number (if you know it): 74 81435002

Reminder

Have you signed the form?

THIS PAGE BLANK (USPTO)

Enter the full names, addresses and postcodes of the inventors in the boxes and underline the surnames

Russell Kennett BULMER

12 The Farthings

Boxmoor

Hemel Hempstead

Hertfordshire

HP1 1XD

United Kingdom

07831258001

Patents ADP number (if you know it):

Patents ADP number (if you know it):

Patents ADP number (if you know it):

Reminder

Have you signed the form?

THIS PAGE BLANK (USPTO)

DISCOVERY OF PHONES ON A NETWORK, SUCH AS A LAN

BACKGROUND OF THE INVENTION

5 The present invention relates to the discovery of devices such as Ethernet phones on a network such as a LAN (Local Area Network) or other network.

The present invention relates to the process of discovery of the devices on a network, that is a network of electronic devices comprising, for example, workstations,
10 personal computers, servers, hubs, routers, bridges, switches, (hereinafter referred to as devices of the network), and links between these devices which may be in the form of physical cable or wireless links. The network may be a local area network (LAN), such as an Ethernet network, wide area network (WAN) or other types, including wireless networks, and may operate in accordance with any desired protocol.

15 Computers and other devices connected to a network may be managed or unmanaged devices. A managed device has processing capability which enables it to monitor data traffic sent from, received at, and passing through the ports of the device. Monitored data associated with the ports of the network device is stored in memory on the
20 network device. For example, data relating to the origin of a data packet which is received at a port is stored along with the identity of the relevant port.

After such a network has been installed, it is desirable for the person appointed network manager to be able to understand the technical operation of the network.

25 In known network management systems, the manner in which the relevant data is retrieved from the managed devices, compiled and displayed ("discovered") has been problematic in several respects. One problem is that the data does not provide information about unmanaged devices.

30 The topology of the network may be deduced by operation of the network manager's computer by the process of discovery in which each of the devices of the network are

interrogated to thereby produce on a network manager's workstation details of the network and its operation, preferably in the form of a network map which may be displayed on a visual display unit showing the devices and links between the devices. At its simplest, and where the device is a "managed" device, this information is usually provided by interrogation using a known protocol, such as, but not limited to, the SNMP (Simple Network Management Protocol), of the so-called 'agent' of each device which stores the device's unique MAC address, the type of device and the MAC addresses embedded in the data passing into a particular port which thereby gives the MAC addresses of the origin of the data and hence the MAC address of the devices which are connected to the ports directly or indirectly.

It has recently been proposed to include so called Ethernet telephones in networks (particularly LANs), in addition to the usual workstations, routers and switches. These Ethernet telephones (which may be controlled by a telephone controller, usually a network call processor (NCP)) allow one to use the existing wiring or other network medium to implement a telephone system. This is particularly useful in a business environment where a single set of cables or other medium may be provided to connect both the computer network and the telephone network.

It is clearly desirable that the network manager of the computer network should be able to similarly view the availability and placement (i.e. the topology) of phones on this same network

A particular difficulty in meeting this objective is that Ethernet phones may not be managed, that is they do not carry an agent as described above. Thus a typical discovery process will not be able to obtain sufficient information about the telephones for details of them to be available to the network manager. At best, they will appear as "generic" devices which have only a MAC address associated with them.

Furthermore, in a typical arrangement of Ethernet phones, a user's PC (personal computer) will be connected through the Ethernet phone to the same port of the network device. Typical discovery processes would simply see two MAC addresses on the same port of the network device, which it would know is impossible, and hence
5 will either (a) highlight the error, or (b) just display them both connected to the port (which is incorrect), or (c) display some item such as a cloud between the port and the phone/PC.

10 SUMMARY OF THE INVENTION

The present inventions provides a method of discovery of devices on a network, which network comprises a plurality of devices, at least some of which are managed, at least one unmanaged phone and telephone controller, said method comprising
15 establishing an address for the managed devices, the telephone controller and the or each said phone, establishing the type of each managed device in the network, determining which of the remaining devices are phones by accessing the relevant information in the discovered telephone controller by establishing correspondence between the or each said phone and its address, and using this information to provide
20 a display of the topology of the network including the or each phone.

The present invention also provides a computer program on a computer readable medium or embodied in a carrier wave for use in discovery of devices on a network, which network comprises a plurality of devices, at least some of which are managed,
25 at least one unmanaged phone, and a telephone controller, said computer program comprising:

- program step for establishing an address for the or each managed device;
- program step for establishing an address for the telephone controller;
- program step for establishing an address for the or each phone;
- 30 program step for establishing the type of each managed device;

program step for determining which of the remaining devices are phones by accessing the relevant information in the discovered telephone controller and establishing correspondence between the or each said phone and its address; and

5 program step for using this information to provide a display of the topology of the network including the or each phone.

Furthermore the present invention may also provide a computer program on a computer readable medium or embodied in a carrier wave for use in discovery of devices on a network, which network comprises a plurality of devices, at least one of
10 which is managed, at least one unmanaged phone, and a telephone controller, said computer program comprising:

a program step to discover the network, including the managed devices, the telephone controller and to establish the MAC addresses of unmanaged phones;

15 a program step to obtain information from the telephone controller containing an association of MAC address(es) to the or each phone (e.g. by loading a WEB page from the telephone controller and including a program step to parse the WEB page to establish correspondence between particular phones and their MAC addresses)

a program step to find ports of devices with MAC address of phones;

20 a program step to determine, in respect of a port on which a MAC address of a phone is present, if there is only a single MAC address;

if yes, a program step to display a phone icon and relevant details connected directly to the port;

25 if no, a program step to determine if there are two MAC addresses and if one is a phone;

if yes, a program step to provide a display of a device with the second MAC address connected to the network via an icon of the phone;

If no, a program step to display an unmanaged aggregator display cloud.

30 According to other aspects the invention provides a computer network comprising a plurality of devices, at least some of which are managed, at least one unmanaged

phone and telephone controller, including means for establishing an address for the managed devices, the telephone controller and the or each said phone, means for establishing the type of each managed device in the network, means for determining which of the remaining devices are phones by accessing the telephone controller and
5 by establishing correspondence between the or each said phone and its address, and means for using this information to provide a display of the topology of the network including the or each phone.

10 BRIEF DESCRIPTION OF THE DRAWINGS

A preferred embodiment of the invention will now be described by way of example only and with reference to the accompanying drawings in which:-

15 Figure 1 is a diagrammatic view of a network incorporating a preferred embodiment of the invention;

Figures 2, 3A, 3B, 4A, 4B, show aspects of the view of part of the network to be described; and

20

Figure 5 is a flow chart of the method of discovery of the Ethernet phones on the network.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

25

Referring to Figure 1 there is shown a physical network 10 comprising a plurality of devices in the form of a network supervisor's workstation or computer 11, other workstations 12B - E, hubs 13A, 13B, switch 14, Ethernet phones 15A-C, phone 15A being directly connected to hub 13A, and phone 15B, 15C being connected
30 between hub 13B and workstation 12E and between hub 13A and workstation 12A respectively and a network call processor (NCP) 20 which operates the telephones 15

over the network. The network is a simple network and is set out for purposes of illustration only. Other configurations and arrangements, may be used.

5 The devices are connected together by means of links 16A – H which may be hard wired and utilise any desired protocol, and link 16F which is a wireless link.

10 The network supervisor's workstation includes, in addition to a visual display unit 18, a central processing unit or signal processor 19, a selector which may be in the form of a mouse 22, a program store 21 which may comprise, for example, a CD drive, a floppy disk drive or a zip drive, and a memory 17 for storing a program which may have been loaded from the program store 21 or downloaded for example via Internet from a website.

15 To discover the network, using a protocol such as SNMP, the network supervisor's computer 11 interrogates each device and analyse the network, and stores in the memory 17 the information relating to the devices within the network and the links between the devices. In essence, many devices include a so-called agent which stores information about the device such as its unique MAC number, its Sys Object ID (which identifies what the device is, what model type it is, how many ports it has and how they are connected), and the MAC address of the origin of the data which at least some of the ports have received and hence to which they are directly or indirectly connected. The computer 11 interrogates the agents of each device to obtain the said information.

20 In a preferred arrangement, the computer 11 may, on command from the selector 22, process signals from the memory 17 by the signal processor 19 and provide on the visual display unit 18 a network map showing each of the devices and the links therebetween. In the examples shown, the network is simple but of course in many instances the network will be considerably more complex and it may be necessary to arrange that the visual display unit 18 only shows a simplified version or only part of the network at any one time.

25

30

As mentioned above, however, whilst the network call processor 20 may support (ie communicate using) a protocol such as the SNMP protocol and hence will be discovered and placed by the computer 11 in its correct location on the network map, the Ethernet phones do not support the SNMP protocol. Thus discovering the network using SNMP (or indeed any other related protocol) will mean that the Ethernet phones will appear as unmanaged generic devices, in other words, the SNMP protocol will not allow for proper discovery of those phones. However although it does not know anything about these generic devices, in the case of Ethernet phones, it does establish their MAC address. The inventors of this invention have discovered that the identity and details of the Ethernet phones 19 can be deduced by using a different system to the rest of the network.

The NCP 20 is a processor which operates the telephones 15 and provides similar services provided by a PBX telephone exchange in, for example, an office network. The NCP 20 includes a memory which contains information (which may be in the form of a custom WEB page) containing a list of the telephones connected to the network, the MAC address of each telephone, the name of the person whose telephone it is, the extension number, etc. Thus, the NCP includes a telephone directory which includes the MAC addresses of each phone.

In order to discover the topology of the Ethernet phones in the network the network supervisor's computer 11 starts by using the steps set out in Figure 5 to determine which MAC addresses belong to which phones (i.e. connects together the MAC addresses of each phone with the information stored on the telephone controller). For example, the WEB page in the telephone controller might typically be arranged so that there is provided a list, the first piece of information on each line being the phone number, the second person using the phone, and the third MAC address. The computer parses through the list and each time it comes to a MAC address (which it recognises from the layout), it then takes the previous two pieces of information for later use.

The initial step is to discover the network as described above and during that discovery process using SNMP it discovers the NCP 20. On discovering that there is an NCP, the computer 11 loads the WEB page from the NCP 20 which contains the list of phones etc. The computer 11 then uses HTML to parse (that is, search) the WEB page to extract the MAC address of each phone and the other information associated with each phone.

In the SNMP discovery process, as part of that process, the MAC addresses of components to which each port of each device is connected have been discovered and this then enables one to put together each telephone MAC address (which, as set out above, have been discovered) and the ports to which it is connected. Thus the discovery process determines where the MAC addresses of each phone have been seen on the network.

Devices with those MAC addresses are marked as being phones and are thus displayed on the network map as telephones and other information such as the name of the person whose phone it is, the extension number, etc may be associated with the phone icon on the network map.

However, there are other difficulties. There are at least two possibilities of the way in which the phone is connected to the network. As illustrated in Figure 2 the Ethernet phones may be directly connected to a port of a managed device by a unique line and thus the process thus far described will produce a network map such as shown in Figure 2 with sufficient information.

On the other hand, Ethernet phones generally have an input port and an output port and could be connected between a managed device and a PC. Thus in that case it will appear to the computer 11 during the discovery process that two or more devices are connected to a single port of a managed device and it can thus be concluded that the basic arrangement is as set out in Figure 4A, that is between the managed device and the PC.

Referring to Figure 3A, if two or more devices are connected to a managed device port via an unmanaged device then 2 or more MAC addresses will have been learnt on the managed device port and the rest of the topology algorithm will have been unable to locate where these MACs are connected to a single unique port. When this happens the topology algorithm assumes these devices, identified by their MAC addresses, are connected via an unmanaged device that the application is unable to discover and resolve. This ambiguity is represented with the two devices being connected via a cloud to the managed device port. (see figure 3B)

With the Ethernet telephones it is possible to connect a desktop device such as a PC to the network via the Ethernet phone (see figure 4A), so that the phone acts as an aggregator or single port hub. This has the advantage of not increasing the number of network connections required to deploy Ethernet Phones. However to keep the cost down phones are unmanaged devices. Hence Ethernet phones and devices connected in this piggy back manner will result in two MAC addresses being seen on the same port of the managed device, and will subsequently be resolved by the topology algorithm as being connected via an unresolved unmanaged aggregating device and hence will be displayed on the map connected to the managed device port via a cloud (See figure 4B)

During the discovery process one discovers the MAC addresses of the Ethernet phones on the network by interrogating the Network Call Processor (NCP) . If there are 2 MACs learnt on a single port and one of them is the MAC address of a Ethernet phone, and the other is the MAC address of a non-phone device (e.g. a personal computer) then it is assumed that, the device uniquely identified by the other MAC is connected to the network via the phone and hence one can eliminate the cloud from the topology and map. (See figure 4A) The result is an accurate representation of the topology with respect to how the phones are connected to the LAN.

We have described how the network may be supervised. The preferred method of the invention is carried out under the control of the network supervisor's workstation or computer and in particular by means of a program controlling the processor apparatus of that computer or elsewhere in the system.

5

The program for controlling the operation of the invention may be provided on a computer readable medium, such as a CD, or a floppy disk, or a zip drive disk carrying the program or their equivalent, or may be provided on a computer or computer memory carrying the website of, for example, the supplier of the network products. The program may be downloaded from whichever appropriate source and used to control the processor to carry out the steps of the invention as described.

10

The program may include:-

15

a program step (which may use a known protocol such as SNMP) to discover the network, including the managed devices, the NCP and to establish MAC addresses of unmanaged phones (Figure 5, step 101);

a program step to change from SNMP to HTTP;

a program step to load a WEB page from the telephone controller;

20

a program step to parse the WEB page of the telephone controller to establish correspondence between particular Ethernet phones and MAC addresses (Figure 5, step 102);

a program step to find ports with MAC address of phones (Figure 5, step 103);

25

a program step to determine, in respect of port on which phone MAC address present, is there only single MAC address? (Step 104);

If yes, a program step display phone icon and relevant details connected directly to the port (Step 105);

30

If no, a program step to determine if there are two MAC addresses and only one is a phone? (Step 106);

If yes, a program step to provide icon of device with second MAC address connected to network via the phone (Step 107);

If no, a program step to display unmanaged aggregator display cloud (ie the situation cannot be resolved) (Step 108)

5

The invention is not restricted to the details of the foregoing example. For example, we have referred to HTML, MAC, SNMP and WEB but these are described as examples. Alternative protocols and arrangements will be apparent.

10

CLAIMS

1. A method of discovery of devices on a network, which network comprises a plurality of devices, at least some of which are managed, at least one unmanaged
5 phone and a telephone controller, said method comprising establishing an address for the managed devices, the telephone controller and the or each said phone, establishing the type of each managed device in the network, determining which of the remaining devices are phones by accessing the relevant information in the discovered telephone
10 controller by establishing correspondence between the or each said phone and its address, and using this information to provide a display of the topology of the network including the or each phone.
2. A method as claimed in claim 1 in which the telephone controller is accessed to obtain information stored in a memory of the telephone controller.
- 15 3. A method as claimed in claims 1 to 2 in which said addresses comprise MAC addresses.
4. A method as claimed in any of claims 1 to 3 including the further step of
20 discovering and displaying the topology of an arrangement wherein a single port of a managed device is connected to a phone and a further non-phone device.
5. A method as claimed in any of claims 1 to 4 including converting information relating to the devices, the telephone controller and the phones into a visual display on
25 a visual display apparatus representing the physical relationship between the devices, for telephone controller and the phones
6. A computer program on a computer readable medium loadable into a digital computer or embodied in a carrier wave, said computer program comprising software
30 for performing the method of any of claims 1 to 5.

7. A computer program on a computer readable medium or embodied in a carrier wave for use in discovery of devices on a network, which network comprises a plurality of devices, at least some of which are managed, at least one unmanaged phone, and a telephone controller, said computer program comprising:

- 5 program step for establishing an address for the or each managed device;
 program step for establishing an address for the telephone controller;
 program step for establishing an address for the or each phone;
 program step for determining which of the remaining devices are phones by
accessing the relevant information in the discovered telephone controller and
10 establishing correspondence between the or each said phone and its address; and
 program step for using this information to provide a display of the topology
of the network including the or each phone.

8. A program as claimed in claim 7 in which the telephone controller is accessed
15 to obtain information stored in a memory of the telephone controller.

9. A program as claimed in claims 7 or 8 in which said addresses comprise the
MAC address.

20 10. A program as claimed in any of claims 7 to 9 including the further program
step of discovering and displaying the topology of an arrangement wherein a single
port of a managed device is connected to an Ethernet phone and a further non-phone
device.

25 11. A program as claimed in any of claims 7 to 10 including the further program
step of converting information relating to the devices, the telephone controller and the
telephones into a visual display on a visual display apparatus representing the physical
relationship between the devices, the telephone controller and the phones.

30 12. A computer program on a computer readable medium or embodied in a carrier
wave for use in discovery of devices on a network, which network comprises a

plurality of devices, at least one of which is managed, at least one unmanaged phone, and a telephone controller, said computer program comprising:

a program step to discover the network, including the managed devices, the telephone controller and to establish the MAC addresses of unmanaged phones;

5 a program step to obtain information from the telephone controller containing an association of MAC address(es) to the or each phone;

a program step to find ports of devices with MAC address of phones;

a program step to determine, in respect of a port on which a MAC address of a phone is present, if there is only single MAC address;

10 if yes, a program step to display a phone icon and relevant details connected directly to the port;

if no, a program step to determine if there are two MAC addresses and if one is a phone;

15 if yes, a program step to provide a display of a device with the second MAC address connected to the network via an icon of the phone;

if no, a program step to display an unmanaged aggregator display cloud.

20 13. A computer program embodied in a carrier wave, said computer program comprising software for performing the method of any of claims 1 to 5.

25 14. A computer network comprising a plurality of devices, at least some of which are managed, at least one unmanaged phone and telephone controller, including means for establishing an address for the managed devices, the telephone controller and the or each said phone, means for establishing the type of each managed device in the network, determining which of the remaining devices are phones by means for
30 accessing the relevant information in the discovered telephone controller by establishing correspondence between the or each said phone and its address, and means for using this information to provide a display of the topology of the network including the or each phone.

15. A computer network as claimed in claim 14 in which the telephone controller is accessed to obtain information stored in a memory of the telephone controller.

THIS PAGE BLANK (USPTO)

3074 GB

1/4




Fig. 1

THIS PAGE BLANK (USPTO)

13074 GB




Figure 2




Figure 3a




Figure 3b

THIS PAGE BLANK (uspto)

3074 GB

3/4




Figure 4a




Figure 4b

THIS PAGE BLANK (USPTO)

3074GB

4/4




Figure 5

THIS PAGE BLANK (USPTO)